



Fortney "CESCO Access Products" for 30+ Years

C-IT - ALL PURPOSE FIRE RATED ACCESS PANEL

C-IT Standard Features:

- Door: 20 gauge (.912 mm thick) cold rolled steel
- Frame: 16 gauge (1.52 mm thick) cold rolled steel with 1" flange
- Hinge: Flush continuous piano hinge
- Latch: Knurled knob/key operated latch bolt
Optional: mortise cylinder preparation (cylinder provided by Cierra or others)
- Finish: Phosphate dipped with factory applied prime coat
Optional: galvanized bonderized steel or stainless steel with #4 satin polish finish
- Insulation: 2" thickness fire rated mineral fiber

C-IT Specifications:

Model C-IT fire rated access panel for all-purpose applications. Access panel shall be model C-IT, size _____ as manufactured by Cierra Products of Minneapolis, MN.

Frame shall be 16 gauge cold rolled steel with 1" flange. Door shall be fabricated from 20 gauge cold rolled steel, insulated sandwich type construction. Door shall be self-latching with automatic closer and interior latch release mechanism. Hinge shall be flush continuous piano type. Latch(es) shall be a knurled knob/key operated latch bolt (optional: preparation to receive 1-1/8" mortise cylinder - cylinder provided by Cierra or others). This assembly shall carry a 1-1/2 hour U.L. "B" label for walls (250 degrees maximum temperature rise, 30 minutes) and carry a 3 hour Warnock Hersey label for ceilings rated 3 hours or less. Finish shall be phosphate dipped with factory applied prime coat (optional: galvanized bonderized steel or stainless steel with #4 satin polish finish).

Installation shall be in accordance with manufacturer's instructions. Manufacturer shall guarantee against defects in material and workmanship for a period of one year.

C-IT Standard Sizes:

| Std sizes (in) | Std Sizes (mm) | Weight/Latches | Std Sizes (in) | Std Sizes (mm) | Weight/Latches |
|----------------|----------------|----------------|----------------|----------------|----------------|
| 06x08 | 203x203 | 11/1 | 22x30 | 559x762 | 32/1 |
| 10x10 | 254x254 | 14/1 | 22x36 | 559x914 | 39/2 |
| 12x12 | 305x305 | 17/1 | 24x24 | 610x610 | 29/1 |
| 12x18 | 305x457 | 25/1 | 24x30 | 610x762 | 36/1 |
| 12x24 | 305x610 | 28/1 | 24x36 | 610x914 | 40/2 |
| 14x14 | 356x356 | 16/1 | 24x48* | 610x1219 | 53/2 |
| 16x16 | 406x406 | 18/1 | 30x30* | 762x762 | 48/1 |
| 18x18 | 457x457 | 20/1 | 32x32* | 813x813 | 51/1 |
| 18x24 | 457x610 | 39/1 | 36x36* | 914x914 | 58/2 |
| 20x30 | 508x762 | 30/1 | 36x48* | 914x1219 | 79/2 |
| 22x22 | 559x559 | 27/1 | 48x48* | 1219x1219 | 100/2 |

All units are hinged on the second dimension (height). Rough opening is door size plus 4".
*Exceeds maximum size to carry a Warnock-Hersey label for ceilings.

Cierra Products